


Clean-Room ESD Stools/Standing-Aid C-WG143HAP / C-WG144HAP

| PRODUCT | DIMENSIONS | C-WG143HAP | C-WG144HAP |
|---|---|--------------------------------|--------------------------------|
|  | Seat depth Seat width Seat height | 390 mm 390 mm 490-690 mm | 390 mm 390 mm 590-840 mm |

TECHNICAL DESCRIPTION

| | |
|-------------|---|
| Seat | Internal structure in multilayered beech wood anatomically shaped, 10 mm thickness. Low formaldehyde emission according to class E1. Covered by a compound of ultra-light integral polyurethane mixed with carbon fibers (PU-Touch ESD). Colour Anthracite GRY-ESD. Non-toxic material and without CFC/HCFC. ESD material conductivity of 10^7 ohm. |
| Mechanism | GS: GAS LIFT, seat height adjustable. |
| Lift action | Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), chrome finish. Class 4 according to DIN 4550. |
| Base | 0902C: 5-star base (Ø 600 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3. |
| Glides | 0331: conductive glides in black nylon (h 32 mm / Ø 50 mm). |

ACCESSORIES

| | |
|---------|--|
| M-0321 | Conductive castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of glides. |
| 0700ESD | Conductive circular footrest (Ø 460 mm), chromed steel ring, supports in black painted steel, height adjustable with a knob. |
| NO-OIL | Gas lift with sealing ring for oil and grease. |